

Multiple Magnetic Stirrer With Heating Technical Data

Model	HHMS-2Max	HHMS-4Max	HHMS-6Max	MHS-4Pro	MHS-6Pro
Picture					
TUSNEWSDOWNLOADCONTACT US					
Control	Asynchronous control (synchronization can be set)				
Number of stirring points	2	4	6	4	6
Max stirring volume	2*2L	4*2L	6*2L	4*500 ML	6*500 ML
Plate materia	Stainless steel with ceramic coating			304 Stainless steel	
Plate temperature	RT - 310℃			RT - 120℃	
Plate size	2-Φ135mm	4-Φ135mm	6-Φ135mm	4-(110*110mm)	6-(110*110mm)
Motor type	Brushless motor				
Mixing direction	Right				
RPM	50-1500RPM	50-1500RPM	50-1500RPM	50 - 1200 RPM	50 - 1200 RPM
Bar size	30 MM				
Display type	LCD liquid crystal display				
Timing	1min-24h	1min-24h	1min-24h	1min-19h59min	1min-19h59min
Voltage	AC110/220V				
Allow ambient temperature	5 - 40℃ 80%RH				
Dimensions	320*245*91 mm	410*320*92 mm	575*340*95 mm	305*225*65 mm	415*225*65 mm